


PIN	
1	VSS
2	VDD
3	VO
4	A0
5	R/W
6	E
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4
12	DB5
13	DB6
14	DB7
15	CS1
16	CS2
17	RST
18	80/68
19	A
20	K

- NOTES:
 1. DRIVE METHOD: 1/64DUTY, 1/9BIAS, VOP 9.6V.
 2. VIEWING ANGLE: 6 O'CLOCK.
 3. DISPLAY TYPE: STN(BLUE), TRANSMISSIVE/NEGATIVE.
 4. OPERATING TEMP: -20 TO 70°C.
 5. STORAGE TEMP: -30 TO 80°C.
 6. CONNECTION: TAB.
 7. IC: ST7565P-T04C*2.
 8. BACKLIGHT: WHITE(3.0V,100mA)LED 5 DIES.
 9. NOT DIMENSION TOLERANCES IS ±0.3.

日期	版本	修改内容
20170426	01	修改公司抬頭為"晶發科技股份有限公司"



晶發科技股份有限公司

GI FAR TECHNOLOGY CO., LTD

DATE	2017.04.26	REV	01
UNIT : mm	Product :	GFB240064A-BNFE-03	
SCALE : 1/1	DRAWN :		
SHEET : 1/1	CHECKED :		
	Hazel	Donlin	PAGE : 1/1